

SPECIFICATIONS

Display		SID001
LCD SIZE		21.5"
ACTIVE AREA		476.64MM (H) X 268.11MM (V)
VIDEO CONTROLLER		T-SUM-V59XUZ1
SCREEN RATIO		16:9
RESOLUTION		1920 X 1080
BRIGHTNESS		250cd/M ²
CONTRAST RATIO		1000:1
RESPONSE TIME		5mS
VIEWING ANGLE		L / R / U / D (85° / 85° / 80° / 80°)
PIXEL SIZE		0.2482MM X 0.2482MM
COLOUR DEPTH		24 BIT - 16.7M COLOURS
VSYNC RANGE		50-75 HZ
HSYNC RANGE		30-80 KHZ
WEIGHT		6KG 13.22LBS
Video		
VGA		DSUB HD15 FEMALE
HDMI		STANDARD 19PIN HDMI
Audio		
INPUT		3.5MM HEADPHONE SOCKET
OUTPUT		3.5MM HEADPHONE SOCKET
SPEAKERS		LEFT + RIGHT
POWER		2x 5W @ 8OHMS
Controls		
USER CONTROL KEYS		7x PUSHBUTTON LOCATED AT BACK OF UNIT
IR CONTROL		YES
Enclosure		
MATERIAL		STEEL/ALUMINIUM
PROTECTIVE COVER		GLASS
DIMENSIONS		301MM X 509.5MM X 44MM 11.85" X 20.05" X 1.73"
MOUNTING		VESA, 100MM x 100MM, M4 x4
FINISH		POWDER COAT
COLOUR		BLACK
Power Supply		
AC INPUT VOLTAGE		UNIVERSAL (110~240VAC 47-63HZ)
AC INPUT CURRENT		1.2A (48W)
POWER FACTOR CORRECTED		NO (EXEMPT <75W)
OPERATING TEMPERATURE		0 TO +70 DEGREES CELSIUS
OPERATING HUMIDITY		20 ~ 90% RH non-condensing
COMPLIANCE		FCC (PART B) CE GS PSE C-TICK ITE